



DLA-118



DLA-218

Specifications

DLA-118

DLA-218

Configuration	Passive	Passive
Rated Power	1200W (RMS)	2400W (RMS)
Construction	18 mm multilayered plywood	18 mm multilayered plywood
LF Driver	1 ´ 18", 4"VC , Ferrite Magnet	2 ´ 18", 4"VC , Ferrite Magnet
Frequency Response (-3dB)	30Hz - 300 Hz	25Hz - 300 Hz
Maximum Peak Output	137 dB	138 dB
Rated Impedance	8W	4W
Dispersion (H ´ V)	Omni	Omni
Connector	2 ´ #NL4R Speakon	2 ´ #NL4R Speakon
Packaging Dimensions (L ´ B ´ H)(cms)	78 ´ 75 ´ 66	
Net Weight	47 kgs	
Gross Weight	50 kgs	



DLA-218A

Specifications

DLA-218A

Configuration	Active
Rated Power	2400W (RMS)
Construction	18 mm multilayered plywood
LF Driver	2 ´ 18", 4"VC , Ferrite Magnet
Frequency Response (-3dB)	25Hz - 300 Hz
Maximum Peak Output	138 dB
Rated Impedance	4W
Dispersion (H ´ V)	Omni
Connector	2 ´ #NL4R Speakon