MDX Series

Professional Channel Mixer

MDX12 / MDX16 / MDX24



- Dual 120 preset Effects, TAP Delay
- 4 Aux, Dual 11 band EQ
- Bluetooth, PC IN - OUT, Recording
- USB Player with Digital display
- Individual +48V phantom power

USB | EQ | MP3 | DSP EFFECT | Bluetooth

Technical Parameter

Microphone input (MIC Preamplifier)	
Type	XLR, balanced, Discrete input circuit
Mic E.I.N.(20Hz- 20kHz)	
@0Ω Source impedance	-134dB/135.7dB A-Weighted
@50Ω Source impedance	-131dB/133.3dB A-Weighted
@150Ω Source impedance	-129dB/130.5dB A-Weighted
Frequency response	<10Hz-150KHz(-1dB) <10Hz-200KHz(-3dB)
Gain range	+10dB to +60dB
Maximum input level	+12dBu@+10dB gain
Impedance	About 2.6KΩ balanced
Signal-to-noise ratio	110dB / 112dB A-Weighted (0dBu In @ +22dB gain)
Distortion (total harmonic distortion+noise)	0.005% / 0.004% A-Weighted
Tpye	6.3mm stereo channel, unbalanced
Impendance	About 20 KΩ unbalanced 10 KΩ unbalanced
Gain range	+10 to -40
Maximum input level	+22dBu@0dB gain



MDX 12
Professional 12 Channel Mixer



MDX 16
Professional 16 Channel Mixer



MDX 24
Professional 24 Channel Mixer

SONOTONE
Innovative Sonic Technology