



DEL-115 A



DEL-215 A



DEL-835 A

Specifications

Rated Power	400W (RMS)	800W (RMS)	1000W (RMS)
Construction	15mm Multilayered Plywood	15mm Multilayered Plywood	15mm Multilayered Plywood
LF Driver	1×15", 3"VC, Ferrite Magnet	2×15", 3"VC, Ferrite Magnet	1×18", 1×15", Ferrite Magnet
HF Driver	1×1.4" exit, 1.75"VC, Ferrite Magnet	1×1.4" exit, 2.5"VC, Ferrite Magnet	1×1.4" exit, 2.5"VC, Ferrite Magnet
Crossover	2.4 kHz	2.2 kHz	500 Hz, 2.2 kHz
Frequency Response (-3dB)	60 Hz - 17 kHz	50 Hz - 17 kHz	38 Hz - 20 kHz
Maximum Peak Output	130 dB	133 dB	134 dB
Dispersion (H × V)	90° × 50°	90° × 50°	90° × 50°
Connector	2 × XLR; 2 × TS mic i/p	2 × XLR; 2 × TS mic i/p	2 × XLR; 2 × TS mic i/p
Packaging Dimensions (L×B×H)	50 × 46 × 78	59 × 52 × 127	67 × 59 × 135
Net Weight	34 kgs	51 kgs	60 kgs
Gross Weight	37 kgs	53 kgs	63 kgs