













CHARGING

MWL Kit is a new product; it is plug-in transmitter. Which is composed of the most advanced and mature high-frequency transmission equipment. It is safe, reliable and easy to use. Each transmitter and receiver can achieve high quality wireless audio transmission. Plug in transmitter can be combined with MWL Kit mobile receiver. The receiver has the same frequency range to choose from and has the same channel library system.

Advantages Of The System:

The transmission line can enter the ready state quickly and conveniently Multiple parallel transmission lines will not interfere with each other

Product Features:

Advanced noise suppression methods

The control tone transmission ensures the safe silence function Up to 50 MHz bandwidth


Good anti intermodulation and anti-interference performance in multi-channel operation mode

Technical Parameters:

Carrier Frequency Band:	500-900 MHz (Select Within This Range)
Frequency Adjustment:	Automatic Tracking Receiver Working Channel @ Infrared Transfer / Manual Adjustment
Output Power:	H= 30mW L= 10mW
Harmonic Radiation:	<55dBc
Input Socket:	XLR Mother Seat
Input Mode:	Condenser Microphone Dynamic Microphone Line In
Frequency Response:	Microphone Mode: 80 Hz - 16000 Hz Line Mode: 30 Hz - 18000 Hz
Maximum Input Voltage:	2.5V @ 1KHz
Maximum Offset	340KHz @ 1KHz
Sensitivity Adjustment:	48dB @ 6dB Stepping
Input Low Cut:	H= 150Hz L= 75Hz
Phantom Output Voltage:	+48V
Use Battery:	AA1.5V / 1.2V Nickel Metal Hydride Battery
Charge:	Type-c Input DC5V @ ≥1000mA
Working Hours:	About 7 Hours
Size:	128mm x 47mm x 47mm
Weight Including Battery:	221 g



DIMENSIONS



FREQUENCY RESPONSE

