

## PA-250

### Description

Designed for use in a wide variety of PA applications. PA-250 is a mixer amplifier of 250 Watts rated output with six unbalanced mic inputs, 2 AUX inputs & a built-in MP3 playback with Tuner facility. Cut-boost type treble and bass controls provided for tonal adjustment. Circuit protector Device has been provided which safeguards the amplifier against overload & short circuit, Temperate dependent speed DC Fan. Output for Box speaker 4, 8 & 16 Ohms/ Driver Unit 70V - 100V has been provided. Easy operation, combined with service accessibility has been optimized in the design.



### Specifications

Model	PA-250
Power Output	340W Max, 250W RMS at 1% THD
Input Channels	6 × Mic/ 2 × Aux / Amp Input 1V/10K
Tone Controls	Bass/Treble
Priority	MIC 1 Priority, MIC 2-6, AUX1-2, Mp3, TUNER
Speaker Output	±4Ω, 8Ω, 16Ω, 70V and 100V
Indicator LEDs	1 Clip, 1 power on
Connectors	JACK Socket, RCA and terminal block
Frequency Response	70Hz-16KHz ± 3dB
Cooling	temp dependant speed DC Fans
Dimensions	433mm × 300mm × 88mm
Net Weight	11 Kg
Gross Weight	12 Kg